

THE G. W. VAN KEPPEL COMPANY

1801 North 9th Street, Kansas City, KS 66101 (913) 281-4800 P.O. Box 2923, Kansas City, KS 66110 Fax (913) 281-0180

PRICING PAGES / SPECIFICATIONS

Item #1 Manufacturer's Standard Crawler Excavator, meeting the net horsepower range of 100 to 130 with 15 to 25 metric ton operating weight rating as advertised in the manufacturer's standard literature, NET DELIVERED PRICE to any District in the State of Missouri, in care of the District General Services Manager (see MoDOT district map attached at back of RFB).

If bidding more than one make or model, make copies of this pricing sheet and submit it with your bid.

I am bidding (MAKE) Volvo		(MODEL) EC140EL
Price \$ 121,988.0	00	
Vendor must complete for each un	<u>it bid</u>	
Net Horse Power: Engine Make: Engine Model: Operating Weight: (lbs) Operating Weight (metric ton) Max Dig Depth:(fl/in) Depth @ 8' bottom: (fl/in) Max. depth of vertical wall (fl/in) Reach @ground level (fl/in) Dump Height (fl/in) Track shoe or rubber shoe width (in) Tail overhang over side (in) Length of track on ground (fl/in)	113 Volvo D4J Tier 4F 31,600 15 18'3" 27'5"	
Warranty Information -		
Standard Warranty:	1 Year	
Extended Warranty:	Optional	
Begin Date:	jangan amang atau dan salah s	

Please indicate if your unit has any of the following equipment options, if the feature is OPTIONAL please provide pricing in the OPTIONS table.

ENGINE: STANDARDOPTIONALNOT AVAILABLE STANDARDOPTIONALNOT AVAILABLE	Hydraulic fan reverser Engine coolant heater
HYDRAULIC SYSTEM: STANDARD Y OPTIONAL NOT AVAILABLE STANDARD OPTIONAL NOT AVAILABLE NOT AVAILABLE	Auxilliary hydraulic lines Auxilliary pilot and electric controls Hydraulic filter restriction indicator kit
UNDERCARRIAGE: STANDARDOPTIONALNOT AVAILABLEX	Triple semi-grouser shoes, 800 mm (32 in.)
STANDARD OPTIONAL NOT AVAILABLE NOT AVAILABLE	Hydraulic Bucket Quick Coupler 30"Heavy Duty Toothed Bucket (with pin(s) if applicable) 36"Heavy Duty Toothed Bucket (with pin(s) if applicable) 50" Smooth Ditching Bucket (with pin(s) if applicable) 72" Smooth Ditching Bucket (with pin(s) if applicable)
FRONT ATTACHMENTS: STANDARD OPTIONAL_X NOT AVAILABLE STANDARD OPTIONAL_X NOT AVAILABLE	Arm, 2.71m minimum (8 ft. 10 in.) Hydraulic Thumb Attachment
STANDARD OPTIONAL NOT AVAILABLE	Counter weight of 2000 lbs. (minimum) at back of unit to counter weight of Hydraulic Bucket Quick Coupler and Hydraulic Thumb Attachment
OPERATOR'S STATION: STANDARD A OPTIONAL NOT AVAILABLE STANDARD OPTIONAL NOT AVAILABLE	Hydraulic oil filter restriction indicator light Protection screens for cab front, rear, and side
STANDARD OPTIONAL NOT AVAILABLE STANDARD OPTIONAL NOT AVAILABLE	LED or strobe type amber beacon light Two lights mounted on cab/ One mounted on the right side of the boom
DIAGNOSTIC CAPABILITIES: STANDARD_X_OPTIONALNOT AVAILABLE STANDARDOPTIONAL X_NOT AVAILABLE	On-board self-diagnostic system for determining source of problems Hardware/software available to allow in-house diagnostic capabilities (if on-board system is not available)

OPTION	DESCRIPTION	Price
	In addition to the MoDOT requested options, please list any vendor- recommended options relevant to this operation. Use additional sheets if necessary.	
Option 1	Lifting Eye Linkage	183.00
Option 2	Dozer Blade	6,688.00
Option 3	30" Triple Grousers	7,879.00

Option 4		
ориол ,	20" Rubber Shoes	8,223.00
Option 5	120V Block Heater	230.00
Option 6	Suspension Seat	849.00
Option 7	Joystick (4 Switch Proportional)	887.00
Option 8	Beacon	119.00
Option 9	Worklights (Extra Front and Rear)	237.00
Option 10	Hydraulic Quick Coupler w/Quick Fit Piping	5403.00
Option 11	36" HD Bucket	2312.00
Option 12	54" Smooth Ditching Bucket	2689.00
Option 13	72" Smooth Ditching Bucket	3203.00
Option 14	Stick Wear Strip	129.00
Option 15	30" HD Bucket	2808.00
Option 16		
Option 17		
Option 18		
Option 19		
Option 20		
		•

Please indicate with an 'X' the disbidding:	stricts (see MoDOT district map attache	d at back of RFB) for which you are
Northwest District (NW) X	Northeast District (NE)	Kansas City (KC) District x
Central District (CD)	St, Louis District (STL)	Southwest District (SW) X
Southeast District (SE)	All Districts	5
(make/model) your compan	parts and options list with detailed by would be willing to provide. Play gested Retail Prices (MSRP) for all exc	ease indicate below the percent (%)
% discount off MSRP for all Da	ata Book or Pricing Guide Options: - S	% Discount 28
Delivery will be made 60-	90 days after rece	eipt of order.

PRICING PAGES / SPECIFICATIONS

Item #1 Manufacturer's Standard Crawler Excavator, meeting the net horsepower range of 100 to 130 with 15 to 25 metric ton operating weight rating as advertised in the manufacturer's standard literature, NET DELIVERED PRICE to any District in the State of Missouri, in care of the District General Services Manager (see MoDOT district map attached at back of RFB).

If bidding more than one make or model, make copies of this pricing sheet and submit it with your bid.

I am bidding (MAKE) Volvo Price \$ 123,922.00 Vendor must complete for each unit bid		(MODEL) ECR145DL/ECR145EL	
		Net Horse Power:	121
Engine Make:	Volvo		
Engine Model:	D4 Tier 4F		
Operating Weight: (lbs)	34,050		
Operating Weight (metric ton)	15.45		
Max Dig Depth:(ft/in)	18 1"		
Depth @ 8' bottom: (ft/in)			
Max. depth of vertical wall (fl/in)			
Reach @ground level (ft/in)	27 ¹ 5 ¹¹		
Dump Height (fl/in)			
Track shoe or rubber shoe width (in)			
Tail overhang over side (in)			
Length of track on ground (ft/in)	· · · · · · · · · · · · · · · · · · ·		
Warranty Information -			
Chundard Manuants	1 Year		
Standard Warranty:	1 lear		
		. A THE PROPERTY OF THE ASSESSMENT OF	
Extended Warranty:	Optional		
Begin Date:			

Please indicate if your unit has any of the following equipment options, if the feature is OPTIONAL please provide pricing in the OPTIONS table.

ENGINI	E:		
STANDARD	OPTIONAL	NOT AVAILABLE	Hydraulic fan reverser
STANDARD	OPTIONAL X	NOT AVAILABLE	Engine coolant heater
HYDRA	ULIC SYSTEM:		
STANDARDX	OPTIONAL	NOT AVAILABLE	Auxilliary hydraulic lines
STANDARD X	OPTIONAL	NOT AVAILABLE	Auxilliary pilot and electric controls
STANDARD X	OPTIONAL	NOT AVAILABLE	Hydraulic filter restriction indicator kit
	CARRIAGE:		
STANDARD	OPTIONAL	NOT AVAILABLE	Triple semi-grouser shoes, 800 mm (32 in.)
BUCKE			STATE OF THE PROPERTY OF A CONTRACTOR
STANDARD	OPTIONAL X	NOT AVAILABLE	Hydraulic Bucket Quick Coupler
STANDARD	OPTIONAL_X	NOT AVAILABLE	30"Heavy Duty Toothed Bucket (with pin(s) if
			applicable)
STANDARD	OPTIONAL	NOT AVAILABLE	36"Heavy Duty Toothed Bucket (with pin(s) if
			applicable)
STANDARD	OPTIONAL	NOT AVAILABLE	50" Smooth Ditching Bucket (with pin(s) if
			applicable)
STANDARD	OPTIONAL	NOT AVAILABLE	72" Smooth Ditching Bucket (with pin(s) if
			applicable)
FRONT	ATT & C!		
	ATTACHMENTS OPTIONAL	NOT AVAILABLE	Arm, 2.71m minimum (8 ft. 10 in.)
STANDARD	OPTIONAL	NOT AVAILABLE	Hydraulic Thumb Attachment
STANDARD	OPTIONAL	NO) AVAILABLE	Hydraulic Linding Armeinnesia
FRAME	.*		
STANDARD	OPTIONAL	NOT AVAILABLE	Counter weight of 2000 lbs. (minimum) at back of
SIMMONUD	OF HORAL	NO! ATAILABLE	unit to counter weight of Hydraulic Bucket Quick
			Coupler and Hydraulic Thumb Attachment
OPERA	TOR'S STATION	1	
STANDARD	OPTIONAL	NOT AVAILABLE	Hydraulic oil filter restriction indicator light
STANDARD	OPTIONAL	NOT AVAILABLE	Protection screens for cab front, rear, and side
		7. T.	
LIGHTS	:		
STANDARD	OPTIONAL	NOT AVAILABLE	LED or strobe type amber beacon light
STANDARD	OPTIONAL	NOT AVAILABLE	Two lights mounted on cab/ One mounted on the
			right side of the boom
DIAGNO	OSTIC CAPABILI	TIES:	
STANDARD	OPTIONAL	NOT AVAILABLE	On-board self-diagnostic system for determining
			source of problems
STANDARD	OPTIONAL	NOT AVAILABLE	Hardware/software available to allow in-house
			diagnostic capabilities (if on-board system is not
			available)
	and the second s		

OPTION	DESCRIPTION	Price
	In addition to the MoDOT requested options, please list any vendor- recommended options relevant to this operation. Use additional sheets if necessary.	
Option 1	Lifting Eye Linkage	183.00
Option 2	Dozer Blade	6688.00
Option 3	30" Triple Grousers	7879.00

20" Rubber Shoes	7983.00
120V Block Heater	230.00
	849.00
Joystick (4 Switch Proportional)	887.00
Beacon	119.00
Worklights (Extra, Front and Rear)	237.00
Hydrualic Quick Coupler w/ Quick Fit Piping	5555.00
36" HD Rucket	2312.00
54" Smooth Ditching Bucket	2689.00
72" Smooth Ditching Bucket	3203.00
Stick Wear Strip	129.00
30" HD Bucket	2808.00
	Suspension Seat Joystick (4 Switch Proportional) Beacon Worklights (Extra, Front and Rear) Hydrualic Quick Coupler w/ Quick Fit Piping 36" HD Bucket 54" Smooth Ditching Bucket 72" Smooth Ditching Bucket Stick Wear Strip 30" HD Bucket

bidding:		ached at back of RFB) for which you are
Northwest District (NW) X	Northeast District (NE)	Kansas City (KC) District X
Central District (CD)x_	St. Louis District (STL)	Southwest District (SW) _x_
Southeast District (SE)	All Dist	ricts
(make/model) your company v	would be willing to provide.	niled pricing information for each Please indicate below the percent (%) excavator options available in your dat
% discount off MSRP for all Data	Book or Pricing Guide Options	:-% Discount 28
Delivery will be made 60-90	days after	receipt of order.

Item #2 Manufacturer's Standard Wheeled Excavator with One-Piece Boom, meeting the net horsepower range of 120 to 160 with 17 to 21 metric ton operating weight rating as advertised in the manufacturer's standard literature, NET DELIVERED PRICE to any District in the State of Missouri, in care of the District General Services Manager (see MoDOT district map attached at back of RFB).

If bidding more than one make or model make copies of this pricing sheet and submit it with your bid.

I am bidding (MAKE) Volvo		(MODEL) <u>EW160E (lpiece Boom)</u>
Price \$ 148,509.	.00	
Vendor must complete for each w	nit hid	
venuor must complete for each an	int Diu	•
Net Horse Power:	150	· ·
Engine Make:	Volvo	
Engine Model:	D6J Tier 4F	
Operating Weight Ibs:	38,030	
Operating Weight: (metric ton)	17.25	
Max Dig Depth:(ft/in)	181711	
Depth @ 8' bottom:(ft/in)		
Max depth of vertical wall (ft/in)		
Reach @ground level (ft/in)	30 ' 2"	
Dump Height (fl/in)		
Blade or Outrigger	Either Available	
Transport width:(ft/in)	:	
Tailswing radius:(fl/in)		
Warranty Information -		
Standard Warranty:	1 Year	
		· · · · · · · · · · · · · · · · · · ·
	•	
1 <u>.</u>		The state of the s
•		
Extended Warranty:	Optional	
	•	

Begin Date:		
Sogni Saro.		

Please indicate if your unit has the following equipment option, if the feature is OPTIONAL please provide pricing in the OPTIONS table.

STANDARD	OPTIONAL	NOT AVAILABLE	Hydraulic Control Pattern Change
SIANDAKD	OPTIONAL	NOI AVAILABLE	nyuraunc Control Pattern Change

OPTION	DESCRIPTION	Price
	In addition to the MoDOT requested option, please list any vendor- recommended options relevant to this operation. Use additional sheets if necessary.	
Option 1	4 Outrigger (1LO Dozer and 2 Outriggers)	4177.00
Option 2	Quick Coupler w/ Quick Fit Piping	5068.00
Option 3	24" HD Bucket	2568,00
Option 4	36" HD Bucket	2796.00
Option 5	48" Smooth Ditching Bucket	2801.00
Option 6	60" Smooth Ditching Bucket	2988.00
Option 7	72" Smooth Ditching Bucket	3089.00

bidding:	ariers (see modor district map attac	net at back of KPD) for which you ar
Northwest District (NW) X	Northeast District (NE)	Kansas City (KC) District X
Central District (CD)	St. Louis District (STL)	Southwest District (SW) X
Southeast District (SE)	All Dist	ricts
(make/model) your company	arts and options list with detail y would be willing to provide. I ested Retail Prices (MSRP) for all ex	Please indicate below the percent (%)
% discount off MSRP for all Da	ta Book or Pricing Guide Options:	- % Discount
Delivery will be made 60-90	days after re	ceipt of order.

Item #3 Manufacturer's Standard Wheeled Excavator with Two-Piece and Telescopic Booms, meeting the net horsepower range of 120 to 160 with 17 to 21 metric ton operating weight rating as advertised in the manufacturer's standard literature, NET DELIVERED PRICE to any District in the State of Missouri, in care of the District General Services Manager (see MoDOT district map attached at back of RFB).

If bidding more than one make or model make copies of this pricing sheet and submit it with your bid.

I am bidding (MAKE) Volvo		(MODEL) EW160E	(2-Piece	Boor
Price \$ 150,330.0	0	· -		
Vendor must complete for each u	nit bid			
Net Horse Power:	150		+ 4	
Engine Make:	Volvo	•		
Engine Model:	D6J Tier 4F	•		
Operating Weight lbs:	38,030		•	
Operating Weight: (metric ton)	17.25			
Max Dig Depth:(ft/in)	18'7"			
Depth @ 8' bottom:(ft/in)				
Max depth of vertical wall (ft/in)		•	•	
Reach @ground level (ft/in)	3012"			
Dump Height (ft/in)				
Blade or Outrigger	Either Available			
Transport width:(fl/in)		•		
Tailswing radius:(ft/in)		•		
, minor, m.S , manufar m.y			4	
Warranty Information -				
	**			
				- 1
Standard Warranty:	1 Year	<u> </u>		* .
				
	•			
Extended Warranty:	Optional			
	î			
			<u> </u>	
Party Pater	•			1
Begin Date:	•			

STANDARD	OPTIONAL NOT AVAILABLE Hydraulic Control Pat	tern Changer
OPTION=	DESCRIPTION	Price
	In addition to the MoDOT requested option, please list any vendor recommended options relevant to this operation. Use additional sheets if necessary.	To the second of
Option 1	4 Outrigger (1LO Dozer and 2 Outriggers)	4177.00
Option 2	Quick Coupler w/ Quick Fit Piping	5068.00
Option 3	24" HD Bucket	2568.00
Option 4	36" HD Bucket	2796.00
Option 5	48" Smooth Ditching Bucket	2801.00
Option 6	60" Smooth Ditching Bucket	2988.00
Option 7	72" Smooth Ditching Bucket	3089.00
Please indica bidding:	ite with an 'X' the districts (see MoDOT district map attached at back o	of RFB) for which you a
Northwest D	istrict (NW) X Northeast District (NE) Kansas	City (KC) District X
Central Dist	rict (CD) St. Louis District (STL) Southw	vest District (SW) X
	strict (SE) All Districts	•

days after receipt of order.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount __

Delivery will be made 60-90